



VHF AIR BAND TRANSCEIVER

IC-A210E



Innovative airband that's easier to install and see in more places

Large, bright OLED display

A fixed mount VHF airband first! The IC-A210E has an organic light emitting diode (OLED) display. The OLED display emits light by itself and the display offers many advantages in brightness, vividness, high contrast, wide viewing angle and response time compared to a conventional display. In addition, the auto dimmer function adjusts the display for optimum brightness at day or night.



Operating information is clearly shown on the OLED display.

Easy channel selection

It's fast and easy to select any of memory channels in the IC-A210E. The "flip-flop" arrow button switches between main and stand-by channels. The dualwatch function allows you to monitor two channels simultaneously. In addition, the auto stack memory stores the last 10 channels used and allows you to recall those channels easily.

GPS memory function

When connected to an external GPS receiver* equipped with an airport frequency database, the frequency data such as nearby airports can be transferred and made available in the IC-A210E.

* Ask your dealer for available GPS receiver details.



Installation example

12V/24V DC power source

The built-in DC-DC converter accepts a 12/24V DC power source. The IC-A210E is easily installed in most airplanes.

Intercom functions

The IC-A210E has a built-in voice activated intercom function allowing the pilot to talk with the copilot via the headset. The IC-A210E has adjustable audio level and squelch control functions.

Easy installation

The IC-A210E neatly fits inside the common mounting brackets used on most airplanes including Icom's IC-A200. Two types of rear-panel adapters are included, allowing for streamlined plug-in connectivity.

* Ask your dealer for compatible panel mount radio details.

8.33kHz channel spacing

In addition to the widely used 25kHz channel spacing, IC-A210E is also compatible with 8.33kHz channel spacing.

Other features

- 10 regular memory channels with a 6-character channel name
- 200 group memory channels (20 Ch×10 banks) with a channel tag
- One touch access to 121.5MHz emergency frequency
- Side tone function for monitoring your voice with headset
- ANL (Automatic noise limiter) function reduces pulse type noise
- Remote control capability
- Time-out-timer
- PC programming capability
- Dial lock and panel lock
- Squelch test function

SPECIFICATIONS

GENERAL

- Frequency coverage : 118.000–136.975MHz
- Frequency spacing : 25kHz, 8.33kHz
- Frequency stability : ±1ppm (0°C to +40°C)
- Operating temperature: -20°C to +55°C
- Antenna impedance : 50Ω
- Number of memory : 10 regular memory, 200 group memory, 10 GPS, 10 auto stack (history) memory
- Power supply requirement : 13.8/27.5V DC (Negative ground)
- Dimensions (W×H×D) : 160×34×271 mm (Projections not included)
- Weight (approx.) : 1.0kg

TRANSMITTER

- Output power : 6W typical (Carrier power)
- Spurious emission :
 - Harmonics : -36dBm (30MHz–1GHz)
 - Except harmonics : -46dBm (30MHz–1GHz)
- Modulation : 85% (Max. 95%)

RECEIVER

- Intermediate frequencies : 1st 38.85MHz, 2nd 450kHz
- Sensitivity AM : -101dBm at 12dB SINAD
- Selectivity :
 - 8.33kHz ch. spacing : 6dB ±2.8kHz
 - 25kHz ch. spacing : 6dB ±8.5kHz
- Spurious rejection : More than 70dB
- Audio output power :
 - External SP : 5W with a 4Ω load
 - Headphone : 60mW with a 500Ω load

Measurements made in accordance with ETSI EN300-676 for Europe version. All stated specifications are and subject to change without notice or obligation.

Supplied Accessories

- Mounting bracket kit
- Rear panel adapter


OPTIONS

MB-53 MOUNTING BRACKET



For mounting the IC-A210E. External speaker (SP-5) and microphone (HM-176) are included.

REAR PANEL VIEW



anfer

RADIOCOMUNICACIONES

info@anfer.com www.anfer.com

Tel. (+34) 963 311 410 Fax. (+34) 963 311 411

Use of the IC-A210E in aircraft requires the appropriate authorization from the respective authorities in each country. Please ask your local Icom dealer for details. Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (01227) 741741
Fax : +44 (01227) 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0211) 346047
Fax : +49 (0211) 333639
E-mail : info@icom-europe.com
URL : <http://www.icom-europe.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejone des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88,
Yong Ding Road, Haidian District,
Beijing, 100039, China
Phone : +86 (010) 5889 5391/5392/5393
Fax : +86 (010) 5889 5395
E-mail : bjicom@bjicom.com
URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolka.com.pl
URL : <http://www.icompolska.com.pl>